

MOBI™ MEDIAN

RODI Pure Water Trolley System

FP-TR1800-03-EU



Recommended For

- ✓ Window Cleaning
- ✓ Solar Panel Cleaning
- ✓ Shopping Centers
- ✓ Courtyards
- ✓ Schools & Campuses

Integrated Flush Valve

A flush valve allows for flushing the membranes in the system extending the life of the RO membranes by removing contaminants such as sediment, rust and bacteria. Which can help to reduce the risk of streaks and spots on windows and solar panels.

We recommend flushing your RO membrane every 2-3 months

Higher Pump Performance & Bigger Filters

Save time and money in the long run with increased filtration capacity allowing for longer filtration cycles and reduced filter changes. With an increased water flow rate a high-performance pump can also deliver water at a higher flow rate, which can be beneficial for cleaning larger areas or for cleaning windows with heavy dirt or grime.



Features	Mobi® Median
Product Code	FP-TR1800-03-EU
Operating Pressure	6.8Bar
Flow Rate (Lpm)	3Lpm*
Filtration	2x 4021 Ro Membranes
TDS Meter	Inline TDS with dual sampling points
Material	Stainless
Power	Mains
Width	500mm
Depth	380mm
Height	1200mm
Weight	35kg



*Performance figures are based on lab testing. Actual results may vary.